

LED LAMP

PURE VISION

LED PAR Series



PV-PAR38, PV-PAR30LN, PV-PAR20



Features & Benefits

Unique halogen looking lens design

Both 25° & 40°, with wide color temperature options*

High CRI (80+), dimmable**

13W replaces 90W halogen, 12W replaces 75W halogen, 7W replaces 50W halogen

25,000 hour average life, Energy Star listed

Enclosed fixture application

Wet location approved

Warranty & Cautions


3-year limited warranty in commercial use from the date of purchase

Operating temperature range between -20°C and +50°C

UL/cUL listed, FCC compliant, RoHS compliant

* PAR30LN, PAR20 5000K ES available, MOQ may apply. ** Check the dimmer compatibility list on our website www.turolight.com

Dimensional drawing



Product Specification

Ordering Code	ES	Model Number	Watts	Base	Voltage (V)	Hour Rating	Beam Angle	Initial Lumens(lm)	CCT(K)	CRI	C.B.C.P. (cd)	Enclosed Fixture Application	Wet Location	Damp Location	M.O.D. (inch)	M.O.L. (inch)	Case QTY.
PV-PAR38																	
1732104	Y	PV-PAR38/13W/27/FL25/D/ES	13	E26	120	25,000	25°	910	2700	80	3698	Y	Y	Y	4.8	5.31	20
1732204	Y	PV-PAR38/13W/30/FL25/D/ES	13	E26	120	25,000	25°	910	3000	80	3698	Y	Y	Y	4.8	5.31	20
1732403	Y	PV-PAR38/13W/40/FL25/D/ES	13	E26	120	25,000	25°	910	4000	80	3698	Y	Y	Y	4.8	5.31	20
1732504	Y	PV-PAR38/13W/50/FL25/D/ES	13	E26	120	25,000	25°	910	5000	80	3698	Y	Y	Y	4.8	5.31	20
1732105	Y	PV-PAR38/13W/27/WFL40/D/ES	13	E26	120	25,000	40°	910	2700	80	1533	Y	Y	Y	4.8	5.31	20
1732205	Y	PV-PAR38/13W/30/WFL40/D/ES	13	E26	120	25,000	40°	910	3000	80	1533	Y	Y	Y	4.8	5.31	20
1732304	Y	PV-PAR38/13W/35/WFL40/D/ES	13	E26	120	25,000	40°	910	3500	80	1533	Y	Y	Y	4.8	5.31	20
1732404	Y	PV-PAR38/13W/40/WFL40/D/ES	13	E26	120	25,000	40°	910	4000	80	1533	Y	Y	Y	4.8	5.31	20
1732505	Y	PV-PAR38/13W/50/WFL40/D/ES	13	E26	120	25,000	40°	910	5000	80	1533	Y	Y	Y	4.8	5.31	20
PV-PAR30LN																	
1732106	Y	PV-PAR30LN/12W/27/FL25/D/ES	12	E26	120	25,000	25°	840	2700	80	2910	Y	Y	Y	3.74	4.84	20
1732206	Y	PV-PAR30LN/12W/30/FL25/D/ES	12	E26	120	25,000	25°	840	3000	80	2910	Y	Y	Y	3.74	4.84	20
1732405	Y	PV-PAR30LN/12W/40/FL25/D/ES	12	E26	120	25,000	25°	840	4000	80	2910	Y	Y	Y	3.74	4.84	20
1732107	Y	PV-PAR30LN/12W/27/WFL40/D/ES	12	E26	120	25,000	40°	840	2700	80	1315	Y	Y	Y	3.74	4.84	20
1732207	Y	PV-PAR30LN/12W/30/WFL40/D/ES	12	E26	120	25,000	40°	840	3000	80	1315	Y	Y	Y	3.74	4.84	20
1732406	Y	PV-PAR30LN/12W/40/WFL40/D/ES	12	E26	120	25,000	40°	840	4000	80	1315	Y	Y	Y	3.74	4.84	20

LED PAR Series

PV-PAR38, PV-PAR30LN, PV-PAR20

Ordering Code	ES	Model Number	Watts	Base	Voltage (V)	Hour Rating	Beam Angle	Initial Lumens(lm)	CCT(K)	CRI	C.B.C.P. (cd)	Enclosed Fixture Application	Wet Location	Damp Location	M.O.D. (inch)	M.O.L. (inch)	Case QTY.
PV-PAR20																	
1732108	Y	PV-PAR20/7W/27/FL25/D/ES	7	E26	120	25,000	25°	500	2700	80	1179	Y	Y	Y	2.47	3.46	50
1732208	Y	PV-PAR20/7W/30/FL25/D/ES	7	E26	120	25,000	25°	500	3000	80	1179	Y	Y	Y	2.47	3.46	50
1732407	Y	PV-PAR20/7W/40/FL25/D/ES	7	E26	120	25,000	25°	500	4000	80	1179	Y	Y	Y	2.47	3.46	50
1732109	Y	PV-PAR20/7W/27/WFL40/D/ES	7	E26	120	25,000	40°	500	2700	80	593	Y	Y	Y	2.47	3.46	50
1732209	Y	PV-PAR20/7W/30/WFL40/D/ES	7	E26	120	25,000	40°	500	3000	80	593	Y	Y	Y	2.47	3.46	50
1732408	Y	PV-PAR20/7W/40/WFL40/D/ES	7	E26	120	25,000	40°	500	4000	80	593	Y	Y	Y	2.47	3.46	50

Ordering Information Example: PV-PAR38/13W/27/FL25/D/ES

LED CLASS	LAMP TYPE	WATTAGE	CCT(K)	BEAM ANGLE	DIMMABLE	ENERGY STAR
PV	PAR38	13W	27, 30	FL25	D	ES
	PAR30LN (Long Neck)	12W	35, 40	WFL40		
	PAR20	7W	50			