

LED LAMP

VIVID Series

Bypass T5 Lamp




VIV-T5BPSP4



Features & Benefits

DLC approved, Frost PET Film, Shatter Protect ¹	120-277V & 347V*, 50000 hour life (L70)
External ballast not required	NSF/ANSI 2 certified**
Double-ended installation	Suitable for splash zones of food equipment
Surge protection	Our safety features allow for installation as well as misapplication protection ²
Replaces T5 HO & T5 HE	¹ ShatterProtect utilizes PET film to reduce the unexpected risk of shattering
180° Beam angle, High CRI (83+)	² For applicable models, see product specification below
5-year limited warranty for DLC listed lamps	**Need to work with NSF certified lighting fixtures
Operating temperature range between -20°C and +45°C	² Contact your local Turolight representative for detail

Dimensional drawing



Product Specification

Ordering Code	DLC	Model Number	Wattage (W)	Voltage (V)	Base	Hour Rating	Beam Angle	Initial Lumen (lm)	CCT(K)	CRI	M.O.L. (inch)	Case QTY.
Replace T5 HO												
1752311	-	VIV-T5BPSP4/12W/35/F (2FT HO)	12	120-277	G5	50,000	180	1450	3500	83	22	8
1752423	-	VIV-T5BPSP4/12W/40/F (2FT HO)	12	120-277	G5	50,000	180	1450	4000	83	22	8
1753300	-	VIV-T5BPSP4/16W/35/F (3FT HO)	16	120-277	G5	50,000	180	1850	3500	83	34	8
1753401	-	VIV-T5BPSP4/16W/40/F (3FT HO)	16	120-277	G5	50,000	180	1850	4000	83	34	8
1754200	Y	VIV-T5BPSP4/25W/30/F (4FT HO)	25	120-277	G5	50,000	180	3200	3000	83	46	25
1754300	Y	VIV-T5BPSP4/25W/35/F (4FT HO)	25	120-277	G5	50,000	180	3200	3500	83	46	25
1754402	Y	VIV-T5BPSP4/25W/40/F (4FT HO)	25	120-277	G5	50,000	180	3300	4000	83	46	25
1754500	Y	VIV-T5BPSP4/25W/50/F (4FT HO)	25	120-277	G5	50,000	180	3400	5000	83	46	25
1754201	Y	VIV-T5BPSP4/25W/30/F/347V (4FT HO)	25	347	G5	50,000	180	3200	3000	83	46	25
1754301	Y	VIV-T5BPSP4/25W/35/F/347V (4FT HO)	25	347	G5	50,000	180	3200	3500	83	46	25
1754403	Y	VIV-T5BPSP4/25W/40/F/347V (4FT HO)	25	347	G5	50,000	180	3300	4000	83	46	25
1754501	Y	VIV-T5BPSP4/25W/50/F/347V (4FT HO)	25	347	G5	50,000	180	3400	5000	83	46	25
Replace T5 HE												
1752305	Y	VIV-T5BPSP4/13W/35/F (4FT HE)	13	120-277	G5	50,000	180	1600	3500	83	46	25
1752413	Y	VIV-T5BPSP4/13W/40/F (4FT HE)	13	120-277	G5	50,000	180	1650	4000	83	46	25

Double-ended Wiring

