

# LED LAMP

VIVID Series



## LED A-Shape Bulbs

VIV-A15, A19, A21, PS25, PS30



15,000hrs: 2-year; 25,000hrs: 3-year limited warranty  
50,000hrs: 5-year limited warranty

Operating temperature range -40 °C ~ +40 °C  
A15 (-20 °C ~ +40 °C)



### Features & Benefits

cULus listed, Energy Star / DLC listed\*

High CRI (80+)\*, dimmable\*


25,000 hrs average life\*

Enclosed fixture application

Damp location approved

\*For applicable models, see product specification below

### Dimensional Drawing



### Ordering Information Example: VIV-A15/5.5W/27/D/F

Family Name	Lamp Type	Wattage	CCT	Dimmable	Others
VIV (Vivid)	A15	5.5W	27 (2700K)	D (Dimmable)	F (Frost)
	A19	6W, 9W, 11W, 15W	30 (3000K)	Blank (Non-dimmable)	E26 (E26 base)
	A21	18W, 23W, 3way	40 (4000K)		EX39 (EX39 base)
	PS25	27W	50 (5000K)		
	PS30 (DLC approved)	36W			

### Product Specification

Ordering Code	Energy Star / DLC	Model Number	Wattage (W)	Base	Voltage (V)	Hour Rating	Beam Angle	Initial Lumens(lm)	CCT(K)	CRI	Enclosed Fixture Application	Damp Location	Dimmable	M.O.D. (inch)	M.O.L. (inch)	Case QTY.
<b>High Lumen VIVID 25000hrs/50000hrs, ES/DLC, -40°C~+40°C</b>																
1754406	Yes	VIV-PS25/27W/40/E26	27	E26	120-277	25,000	230°	3200	4000	80	Y	Y	N	3.23	6.73	40
1755404	Yes DLC	VIV-PS30/36W/40/EX39	36	EX39	120-277	50,000	230°	4500	4000	80	Y	Y	N	3.74	7.28	40
1764210	Yes	VIV-A21/23W/30/D	23	E26	120	15,000	230°	2550	3000	80	Y	Y	Y	2.63	4.8	40
1753200	Yes	VIV-A21/90/18W/30/D (CRI 90)	18	E26	120	25,000	230°	2000	3000	90	Y	Y	Y	2.63	4.8	40
1763232	Yes	VIV-A21/3WAY/15W/27/D	15/10/5	E26	120	15,000	230°	1600/1100/600	2700	80	Y	Y	Y	2.63	4.8	40

# LED A-Shape Bulbs

VIV-A15, A19, A21, PS25, PS30

Ordering Code	Energy Star / DLC	Model Number	Wattage (W)	Base	Voltage (V)	Hour Rating	Beam Angle	Initial Lumens(lm)	CCT(K)	CRI	Enclosed Fixture Application	Damp Location	Dimmable	M.O.D. (inch)	M.O.L. (inch)	Case QTY.
<b>A15 VIVID 25000hrs ES</b>																
1752105	Yes	VIV-A15/5.5W/27/D/F	5.5	E26	120	25,000	220°	450	2700	80	Y	Y	Y	-	3.3	100
1752219	Yes	VIV-A15/5.5W/30/D/F	5.5	E26	120	25,000	220°	450	3000	80	Y	Y	Y	-	3.3	100
1752420	Yes	VIV-A15/5.5W/40/D/F	5.5	E26	120	25,000	220°	450	4000	80	Y	Y	Y	-	3.3	100
<b>A19 VIVID X18 Dimmable 25000hrs, ES, Enclosed Fixtures, -40°C~+40°C</b>																
1762021	Yes	VIV-A19/X18/15W/27/D	15	E26	120	25,000	220°	1600	2700	80	Y	Y	Y	-	4.9	40
1762797	Yes	VIV-A19/X18/15W/30/D	15	E26	120	25,000	220°	1600	3000	80	Y	Y	Y	-	4.9	40
1762879	Yes	VIV-A19/X18/15W/40/D	15	E26	120	25,000	220°	1600	4000	80	Y	Y	Y	-	4.9	40
1762549	Yes	VIV-A19/X18/15W/50/D	15	E26	120	25,000	220°	1600	5000	80	Y	Y	Y	-	4.9	40
1762798	Yes	VIV-A19/X18/11W/30/D	11	E26	120	25,000	220°	1100	3000	80	Y	Y	Y	-	4.4	40
1762880	Yes	VIV-A19/X18/11W/40/D	11	E26	120	25,000	220°	1100	4000	80	Y	Y	Y	-	4.4	40
1762019	Yes	VIV-A19/X18/9W/27/D	9	E26	120	25,000	220°	800	2700	80	Y	Y	Y	-	4.4	40
1762799	Yes	VIV-A19/X18/9W/30/D	9	E26	120	25,000	220°	800	3000	80	Y	Y	Y	-	4.4	40
1762881	Yes	VIV-A19/X18/9W/40/D	9	E26	120	25,000	220°	800	4000	80	Y	Y	Y	-	4.4	40
1762550	Yes	VIV-A19/X18/9W/50/D	9	E26	120	25,000	220°	800	5000	80	Y	Y	Y	-	4.4	40
1762020	Yes	VIV-A19/X18/6W/27/D	6	E26	120	25,000	220°	480	2700	80	Y	Y	Y	-	4.2	40
1762700	Yes	VIV-A19/X18/6W/30/D	6	E26	120	25,000	220°	480	3000	80	Y	Y	Y	-	4.2	40
1762882	Yes	VIV-A19/X18/6W/40/D	6	E26	120	25,000	220°	480	4000	80	Y	Y	Y	-	4.2	40