



Philips EnduraLED
PAR38 Series 800
Dimmable Indoor Flood
LED Lamps

*Ideal for general and accent
lighting in retail, hospitality,
and residential spaces*

EnduraLED

Multiple beam angle LED retrofits with improved lumens accent in style

Philips EnduraLED PAR38 Series 800 Dimmable Indoor Flood LED Lamps with smooth dimming are perfect for track and recessed lighting. Their improved lumens provide more “punch” where you need it.

High efficacy dimmable LED reflector lamp

- Smooth dimming to 10% of full light levels*
- Instant-on light
- Emits virtually no UV/IR light in the beam
- 45,000 hour rated average life¹
- Crisp, uniform beam highlight merchandise or illuminate general areas
- 17W PAR38 saves 43 watts of energy when compared to a 60W halogen PAR38**
- Available in 2700K, 3000K and 4000K color temperatures
- Increased candela (MBCP) creates more application options
- Contains no mercury

Easy to experience

- Available in multiple beam angles: 10°, 15°, 22°, 36°
- Lowers maintenance costs by reducing re-lamp frequency
- Will not fade colors, avoids inventory spoilage
- 3-year limited warranty

(1, *, ** See back page for footnotes)

PHILIPS

sense

simplicity

Philips EnduraLED PAR38 Series 800 Dimmable Indoor Flood LED Lamps

Ordering, Electrical and Technical Data (Subject to change without notice)

| Product Number | Ordering Code | Nom. Watts | Volts | Lamps per SKU | Description | Bulb Type | Base | Rated Avg. Life (Hrs.) ¹ | Approx. Lumens ² | Approx. MBSCP ^{2,3} | CRI | Color Temp. (Kelvin) | MOL (In.) |
|----------------|------------------------------|------------|-------|---------------|---------------------------------------|-----------|--------|-------------------------------------|-----------------------------|------------------------------|-----|----------------------|-----------|
| 41017-5 | 17PAR38/END/F22 2700 DIM 6/1 | 17 | 120 | 1 | 120V EnduraLED 17W Dimmable PAR38 22° | PAR38 | Medium | 45,000 | 880 | 3900 | 85 | 2700 | 5.2 |
| 41018-3 | 17PAR38/END/F22 3000 DIM 6/1 | 17 | 120 | 1 | 120V EnduraLED 17W Dimmable PAR38 22° | PAR38 | Medium | 45,000 | 930 | 4100 | 85 | 3000 | 5.2 |
| 41019-1 | 17PAR38/END/F22 4000 DIM 6/1 | 17 | 120 | 1 | 120V EnduraLED 17W Dimmable PAR38 22° | PAR38 | Medium | 45,000 | 1050 | 4800 | 75 | 4000 | 5.2 |
| 41443-3 | 17PAR38/END/S10 3000 DIM 6/1 | 17 | 120 | 1 | 120V EnduraLED 17W Dimmable PAR38 10° | PAR38 | Medium | 45,000 | 930 | 14000 | 82 | 3000 | 5.3 |
| 41451-6 | 17PAR38/END/S15 2700 DIM 6/1 | 17 | 120 | 1 | 120V EnduraLED 17W Dimmable PAR38 15° | PAR38 | Medium | 45,000 | 880 | 7200 | 84 | 2700 | 5.3 |
| 41453-2 | 17PAR38/END/S15 4000 DIM 6/1 | 17 | 120 | 1 | 120V EnduraLED 17W Dimmable PAR38 15° | PAR38 | Medium | 45,000 | 1080 | 9600 | 78 | 4000 | 5.3 |
| 41460-7 | 17PAR38/END/F36 2700 DIM 6/1 | 17 | 120 | 1 | 120V EnduraLED 17W Dimmable PAR38 36° | PAR38 | Medium | 45,000 | 880 | 1500 | 84 | 2700 | 5.3 |
| 41461-5 | 17PAR38/END/F36 3000 DIM 6/1 | 17 | 120 | 1 | 120V EnduraLED 17W Dimmable PAR38 36° | PAR38 | Medium | 45,000 | 930 | 1600 | 82 | 3000 | 5.3 |

Shipping Data (Subject to change without notice)

| Product Number | SKU UPC (0-46677) | Outer Bar Code (5-00-46677) | Case Qty. | Case Weight (lbs.) | Case Cube (cu. ft.) | Pallet Qty. | SKUs Per Layer | Layers High | SKU Dimensions (W x D x H)(In.) | Case Dimensions (W x D x H)(In.) | Pallet Dimensions (W x D x H)(In.) |
|----------------|-------------------|-----------------------------|-----------|--------------------|---------------------|-------------|----------------|-------------|---------------------------------|----------------------------------|------------------------------------|
| 41017-5 | 41017-9 | 41017-4 | 6 | 9.14 | 0.641 | 324 | 54 | 6 | 5.1 x 5.1 x 5.7 | 10.8 x 16.1 x 6.4 | 37.7 x 42.9 x 38.3 |
| 41018-3 | 41018-6 | 41018-1 | 6 | 9.14 | 0.641 | 324 | 54 | 6 | 5.1 x 5.1 x 5.7 | 10.8 x 16.1 x 6.4 | 37.7 x 42.9 x 38.3 |
| 41019-1 | 41019-3 | 41019-8 | 6 | 9.14 | 0.641 | 324 | 54 | 6 | 5.1 x 5.1 x 5.7 | 10.8 x 16.1 x 6.4 | 37.7 x 42.9 x 38.3 |
| 41443-3 | 41443-6 | 41443-1 | 6 | 10.5 | 0.641 | 270 | 54 | 5 | 5.1 x 5.1 x 5.8 | 15.9 x 10.8 x 6.4 | 47.2 x 39.4 x 38.0 |
| 41451-6 | 41451-1 | 41451-6 | 6 | 10.5 | 0.641 | 270 | 54 | 5 | 5.1 x 5.1 x 5.8 | 15.9 x 10.8 x 6.4 | 47.2 x 39.4 x 38.0 |
| 41453-2 | 41453-5 | 41453-0 | 6 | 10.5 | 0.641 | 270 | 54 | 5 | 5.1 x 5.1 x 5.8 | 15.9 x 10.8 x 6.4 | 47.2 x 39.4 x 38.0 |
| 41460-7 | 41460-3 | 41430-8 | 6 | 10.5 | 0.641 | 270 | 54 | 5 | 5.1 x 5.1 x 5.8 | 15.9 x 10.8 x 6.4 | 47.2 x 39.4 x 38.0 |
| 41461-5 | 41461-0 | 41461-5 | 6 | 10.5 | 0.641 | 270 | 54 | 5 | 5.1 x 5.1 x 5.8 | 15.9 x 10.8 x 6.4 | 47.2 x 39.4 x 38.0 |

1) Rated average life based on engineering testing and probability analysis.

2) Photometric testing consistent with IES LM-79.

3) Maximum Beam Candlepower.

* Designed for "Leading Edge" TRIAC dimming systems.

† Light output of the 17W PAR38 at 880 lumens and 3500 candela compares to the 60W Halogen PAR38 at 880 lumens and 3200 candela.

Energy Efficiency

Estimated Lighting Costs Using a Standard 60W Halogen PAR38

| | |
|--------------------------|---------------------------------------|
| Present Wattage | 60 W |
| x Annual Operating Hours | 3000 hrs |
| | = 180,000 watts per year |
| ÷ 1,000 | = 180 kWh per year |
| x kWh rate of \$0.10 | = \$18 per year |
| x 100 lamps per space | = \$1800 annual energy cost per space |

| | |
|--------------------------|--------------------------------------|
| Present Wattage | 17 W |
| x Annual Operating Hours | 3000 hrs |
| | = 51,000 watts per year |
| ÷ 1,000 | = 51 kWh per year |
| x kWh rate of \$0.10 | = \$5.10 per year |
| x 100 lamps per space | = \$510 annual energy cost per space |

Total Estimated Annual Savings⁰ = \$1,290

⁰ Based on 100 lamps per space operating at 3,000 hours per year.

WARNINGS AND CAUTIONS

- Suitable for use in open luminaires (fixtures).
- Do not use in outdoor fixtures.
- Do not use in enclosed fixtures.
- Turn off power before changing lamp.

CAUTION: Risk of electric shock.

Use in dry location only.

NOTES: This device complies with Part 18 of the FCC rule.

This product may cause interference with other devices. If interference occurs, change the location of the products involved. This RFLD device complies with Canadian ICES-005.

This energy saving example shows an application of 100 lamps in a space currently using a 60W halogen PAR38, operating 3,000 hours per year at a cost of \$0.10 per kWh.[†] Your actual savings may vary depending on the energy costs in your geographic location.

Replacing 100 halogen 60W PAR38 lamps with the Philips 17W EnduraLED PAR38 can provide significant energy cost savings of \$1,290 per year! Potential savings from the reduction in HVAC costs as a result of using a lower wattage lamp that emits less heat is an additional benefit not included in this example.

[†] Light output of the 17W PAR38 at 880 lumens and 3500 candela compares to the 60W Halogen PAR38 at 880 lumens and 3200 candela.



LISTED
LED LAMPS 3 PRR E317295



© 2011 Philips Lighting Company. A Division of Philips Electronics North America Corporation. All rights reserved. Printed in USA 4/11

P-6247

www.philips.com

Philips Lighting Company
200 Franklin Square Drive
Somerset, NJ 08873
1-800-555-0050

Philips Lighting
281 Hillmount Road
Markham, Ontario
Canada L6C 2S3
1-800-555-0050
A Division of Philips Electronics Ltd.