

STJ Tracks

2', 4', 6', 8', 12'



SPECIFICATION

A myriad of configurations are possible with these 120V/20A rated commercial grade track sections. Low profile track cross-section; an economic solution for most applications.

Track has solid copper conductors with Noryl® insulators placed in heavy 14 ga. extruded aluminum channels.

Mechanical polarity with a visual indicator simplifies installation and mounting of fixtures while assuring proper electrical connections. All Stanpro track fixtures have two position contacts to access 1-circuit conductors.

Toggle bolts are supplied for simple surface installation. 2', 4', and 6' sections supplied with (2) toggle bolts, 8' and 12' sections supplied with (3) toggle bolts.


All track sections are supplied with two insulated end caps.

LISTING

cULus listed. Suitable for dry locations.

()	Te and the second se
3 colors available: Black – White – Silver	10

DIMENSIONS



Track J – Track Section View



ORDERING GUIDE		
STJ	-	_
Series	Circuit section length	Finish
STJ	2 - 2' (24") length; 20-1/8" actual length 4 - 4' (48") length; 44-1/8" actual length 6 - 6' (72") length; 68-1/8" actual length 8 - 8' (96") length; 92-1/8" actual length 12 - 12' (144") length; 140-1/8" actual length	BK - Black WH - White SI - Silver

J track is standard.

For J2, H and H2 tracks, please contact factory for more informations.





Contractor: