



Choose the right lamp for your application. STANDARD CFL are available in decorative shapes as well. They are suitable for outdoor\* applications (base up) and in enclosed\*\* fixtures. Operating temperatures: -23°C/-10°F to 55°C/131°F

A shape



Capsules



| Order code       | Description               | Watts (W)   | Base   | Colour temp. (K) | CRI | Average life (hrs) | Initial lumens (lm) | Case qty | Incandescent equivalent (W) |
|------------------|---------------------------|---|--|------------------|-----|--------------------|---------------------|----------|-----------------------------|
| <b>A Shape</b>   |                           | 4 W: MOL : 4 1/8 in. (103 mm)<br>9 W: MOL : 4 7/8 in. (113 mm)<br>14 W and 16 W: MOL : 4 7/8 in. (124 mm) | Dia. : 2 7/8 in. (53 mm)<br>Dia. : 2 7/8 in. (55 mm)<br>Dia. : 2 7/8 in. (60 mm) |                  |     |                    |                     |          |                             |
| 58445            | CF4/27K/A15/E26/STD       | 4   | E26  | 2 700            | 82  | 8 000              | 225                 | 25       | 25                          |
| 58446            | CF9/27K/A16/E26/STD */**  | 9   | E26  | 2 700            | 82  | 8 000              | 470                 | 40       | 40                          |
| 58394            | CF14/27K/A19/E26/STD */** | 14  | E26  | 2 700            | 82  | 8 000              | 800                 | 60       | 60                          |
| <b>Capsules*</b> |                           | 15 W: MOL : 5 1/2 in. (140 mm)<br>20 W and 26 W: MOL : 6 3/8 in. (162 mm)                                 | Dia. : 2 3/8 in. (60 mm)<br>Dia. : 2 7/8 in. (73 mm)                             |                  |     |                    |                     |          |                             |
| 56268            | CF15/27K/T19/E26/STD      | 15  | E26  | 2 700            | 82  | 8 000              | 800                 | 60       | 60                          |
| 58395            | CF15/30K/T19/E26/STD      | 15  | E26  | 3 000            | 82  | 8 000              | 800                 | 60       | 60                          |
| 58396            | CF15/41K/T19/E26/STD      | 15  | E26  | 4 100            | 82  | 8 000              | 800                 | 60       | 60                          |
| 56269            | CF15/50K/T19/E26/STD      | 15  | E26  | 5 000            | 82  | 8 000              | 800                 | 60       | 60                          |
| 56270            | CF20/27K/T19/E26/STD      | 20  | E26  | 2 700            | 82  | 8 000              | 1 200               | 75       | 75                          |
| 58400            | CF20/30K/T19/E26/STD      | 20  | E26  | 3 000            | 82  | 8 000              | 1 350               | 75       | 75                          |
| 58401            | CF20/41K/T19/E26/STD      | 20  | E26  | 4 100            | 82  | 8 000              | 1 350               | 75       | 75                          |
| 56271            | CF20/50K/T19/E26/STD      | 20  | E26  | 5 000            | 82  | 8 000              | 1 200               | 75       | 75                          |
| 56272            | CF26/27K/T23/E26/STD      | 26  | E26  | 2 700            | 82  | 8 000              | 1 450               | 100      | 100                         |
| 56273            | CF26/50K/T23/E26/STD      | 26  | E26  | 5 000            | 82  | 8 000              | 1 450               | 100      | 100                         |

# Decorative Lamps



Candles



Globes



| Order code     | Description               | Watts (W)   | Base   | Colour temp. (K) | CRI | Average life (hrs) | Initial lumens (lm) | Case qty | Incandescent equivalent (W) |
|----------------|---------------------------|---|--|------------------|-----|--------------------|---------------------|----------|-----------------------------|
| <b>Candles</b> |                           | 3 W and 5 W: MOL : 4 1/2 in. (112 mm)<br>7 W and 9 W: MOL : 4 1/2 in. (122 mm)    | Dia. : 1 1/2 in. (36 mm)<br>Dia. : 1 1/2 in. (40 mm) |                  |     |                    |                     |          |                             |
| 58413          | CF3/27K/CANDLE/E26/STD    | 3   | E26  | 2 700            | 82  | 8 000              | 80                  | 100      | 15                          |
| 59841          | CF5/T2/27K/CANDLE/E12/STD | 5   | E12  | 2 700            | 82  | 8 000              | 220                 | 96       | 25                          |
| 59842          | CF5/T2/27K/CANDLE/E26/STD | 5   | E26  | 2 700            | 82  | 8 000              | 220                 | 96       | 25                          |
| 14167          | CF7/27K/CANDLE/E12/STD    | 7   | E12  | 2 700            | 82  | 8 000              | 350                 | 96       | 30                          |
| 14168          | CF7/27K/CANDLE/E26/STD    | 7   | E26  | 2 700            | 82  | 8 000              | 350                 | 96       | 30                          |
| 59843          | CF9/T2/27K/CANDLE/E12/STD | 9   | E12  | 2 700            | 82  | 8 000              | 450                 | 96       | 40                          |
| 59844          | CF9/T2/27K/CANDLE/E26/STD | 9   | E26  | 2 700            | 82  | 8 000              | 450                 | 96       | 40                          |
| <b>Globes*</b> |                           | 9 W and 14 W: MOL : 4 1/2 in. (110 mm)<br>20 W and 25 W: MOL : 5 1/2 in. (143 mm) | Dia. : 2 1/2 in. (64 mm)<br>Dia. : 3 3/4 in. (95 mm) |                  |     |                    |                     |          |                             |
| 58439          | CF9/27K/G25/E26/STD */**  | 9   | E26  | 2 700            | 82  | 8 000              | 495                 | 48       | 40                          |
| 58440          | CF14/27K/G25/E26/STD */** | 14  | E26  | 2 700            | 82  | 8 000              | 850                 | 48       | 40                          |
| 61140          | CF20/27K/G30/E26/STD      | 20  | E26  | 2 700            | 82  | 8 000              | 1 100               | 48       | 60                          |
| 57192          | CF25/27K/G30/E26/STD      | 25  | E26  | 2 700            | 82  | 8 000              | 1 300               | 48       | 60                          |



Visit our website for a complete listing of all STANDARD ENERGY STAR qualified products.