



SlimSurface LED Downlight

SlimSurface LED downlight, 7-inch round, surface mount, 80 CRI, 3000K CCT, 1000 lm, 120V, Standard (TRIAC) dimming, wet location, Matte White Finish

SlimSurface LED downlight, 7-inch round, surface mount, 80 CRI, 3000K CCT, 1000 lm, 120V, Standard (TRIAC) dimming, wet location, Matte White Finish - 71 lm/W

SlimSurface LED is a low profile downlight intended for ceiling or wall mount applications. This 0.625" thick luminaire offers the appearance of a recessed downlight but is actually surface mounted.

Product data

General Information	
Lamp Source Code	LED
Colour Temperature	3000K
CRI	80
Downlight Type	Open Downlight
Photometric Distribution Type	Direct
Mounting	Surface Wall
Operating and Electrical	
Voltages	120 V
Luminaire Input Watts	14

Mechanical and Housing	
Aperture Size Code	7 in
Shape	Round
Initial Performance (IEC Compliant)	
Luminaire Lumens	1000
Efficacy	71 lm/W
Product Data	
Order product name	SlimSurface LED downlight, 7-inch round, surface mount, 80 CRI, 3000K CCT, 1000 lm, 120V, Standard (TRIAC) dimming, wet location, Matte White Finish

SlimSurface LED Downlight

Order code	S7R830K10
Material Nr. (12NC)	LIGU60011118
Catalog Number	S7R830K10
Catalog Number Description	SlimSurface LED downlight, 7-inch round, surface mount, 80 CRI, 3000K CCT, 1000 lm,120V, Standard (TRIAC) dimming, wet location, Matte White Finish

