



Core & Coil (71A) MH ~LT~ 175W

CORE & COIL HID MH BAL 70W M98/143 120/277/347V KIT

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

General Information					
ANSI Code	M98-M143				
Lamp Type	70W MH				
Number of Lamps	1 piece/unit				
Circuit Type	HX-HPF				
Ballast Type	Magnetic HID				
Base Model	71A52A2				
Core Size	3 X 4 (2 coil)				
Suitable For Outdoor Use	Yes				
Ignitor Catalog Number	LI533-H4				
Ignitor Temperature Rating	105°C				
Capacitor Value	8 MFD				
Capacitor Catalog Number	7C080L30RA				
Capacitor Requirements	280V				
Capacitor Temperature Rating	105°C				
Capacitor Diameter/Oval Dimensions	1.25 in				
Capacitor Height	2.75 in				
Automatic Restart	No				

Operating and Electrical						
Input Voltage	120/277/347 V					
Input Frequency	60 Hz					
Input Current (Open Circuit)	1.9/0.8/0.65 A					
Input Current (Starting)	0.55/0.25/0.2 A					
Input Current (Short Circuit)	0.55-0.8/0.25-0.45/0.2-0.35 A					
Secondary Short Circuit Current	0.95-1.25 A					
Constant Wattage Deviation	10%					
Ballast Factor (Nom)	1					
Power Factor (Nom)	0.90					
Open Circuit Voltage	255 V					
Input Current (Nom)	0.81/0.35/0.28 A A					
Input Power (Nom)	88 W					
Rated Lamp Power	70 W					
Wiring						
Wire Striplength	0.5 mm					
Wire Length by Color	12"					
Wire Type	Stranded					
Remote Wiring Configuration Allowed	Yes					


Datasheet, 2019, March 22 data subject to change

Core & Coil (71A) MH ~LT~ 175W

Max Ballast-Lamp Distance Remote	15'				
Wiring					
Recommended Fuse Value	4/2/2 A				
Approval and Application					
Open Circuit Voltage Test (Volts)	230-280 V				
Approval Marks	ULR CSA certificate RoHS Compliant				
Temperature Marking	A/A/A				
UL Recognized	Yes				
Hipot Test (1 Minute)	2000 V				
Hipot Test (2 Seconds)	2500 V				
UL Insulation Class	H(180°C)				
UL Temperature Code	1029A				

Product Data				
Order product name	CORE & COIL HID MH BAL 70W M98/143			
	120/277/347V KIT			
EAN/UPC - Product	781087078150			
Order code	192831			
Local order code	192831			
Numerator - Quantity Per Pack	1			
Numerator - Packs per outer box	1			
Material Nr. (12NC)	913700532109			
Net Weight (Piece)	2.572 kg			

Dimensional drawing



MH BAL 70W M98/143 120/277/347V KIT

Product	C1	C2	A1	A2	B1	B2
CORE & COIL HID MH BAL 70W	2.75 in	1.45 in	3.9 in	3.5 in	2.8 in	2.4 in
M98/143 120/277/347V KIT						

