

LED LAMP

VIVID Series




VIV-T8DFSP4



Features & Benefits

DLC approved, high lumen efficiency	NSF/ANSI 2 Certified ¹
Plastic end caps, glass tube with PET cover	Suitable for splash zones of food equipment
50,000 hour life (L70), 180° Beam angle, High CRI (83+)	Fits into existing linear fixtures
Direct replacement for T8 linear fluorescent	Compatible with most Instant Start Ballast ² with input voltage of 120-277V and 347V

Dimensional drawing



Warranty & Cautions

¹Need to work with NSF certified lighting fixtures
²For detail, you may contact your sales person or check www.turolight.com for ballast compatibility list

5-year limited warranty for DLC listed lamps / 3-year limited warranty for non-DLC*

Bulb wall temperature range between -20°C and +45°C

Not recommended to use with ballast 5 years or older

*Please check the "Turolight LED Limited Warranty" for details
 FCC Note: This device complies with Part 18 of the FCC Rules.

Product Specification

Ordering Code	DLC	Model Number	Nominal Lamp Power (Watts)	System Power (Watts)			Initial Lumen (lm)			Base	Voltage (V)	Hour Rating	Beam Angle	CCT(K)	CRI	M.O.L. (inch)	Case QTY.
				Low BF (0.78)	Normal BF (0.88)	High BF (1.16)	Low BF (0.78)	Normal BF (0.88)	High BF (1.16)								
1762785	-	VIV-T8DFSP4/9W/30/F	9	9	12	17	850	1250	1950	G13	120-277, 347	50,000	180	3000	83	24	25
1762364	-	VIV-T8DFSP4/9W/35/F	9	9	12	17	900	1300	2000	G13	120-277, 347	50,000	180	3500	83	24	25
1762867	Y	VIV-T8DFSP4/9W/40/F	9	9	12	17	950	1350	2050	G13	120-277, 347	50,000	180	4000	83	24	25
1762543	Y	VIV-T8DFSP4/9W/50/F	9	9	12	17	1000	1400	2100	G13	120-277, 347	50,000	180	5000	83	24	25
1762735	Y	VIV-T8DFSP4/13W/30/F	13	13	16	22	1400	1800	2500	G13	120-277, 347	50,000	180	3000	83	48	25
1762339	Y	VIV-T8DFSP4/13W/35/F	13	13	16	22	1450	1850	2550	G13	120-277, 347	50,000	180	3500	83	48	25
1762822	Y	VIV-T8DFSP4/13W/40/F	13	13	16	22	1500	1900	2600	G13	120-277, 347	50,000	180	4000	83	48	25
1762524	Y	VIV-T8DFSP4/13W/50/F	13	13	16	22	1600	2000	2700	G13	120-277, 347	50,000	180	5000	83	48	25
1762736	Y	VIV-T8DFSP4/15W/30/F	15	15	18	24	1600	2000	2700	G13	120-277, 347	50,000	180	3000	83	48	25
1762340	Y	VIV-T8DFSP4/15W/35/F	15	15	18	24	1600	2000	2700	G13	120-277, 347	50,000	180	3500	83	48	25
1762823	Y	VIV-T8DFSP4/15W/40/F	15	15	18	24	1800	2200	2950	G13	120-277, 347	50,000	180	4000	83	48	25
1762525	Y	VIV-T8DFSP4/15W/50/F	15	15	18	24	1900	2300	3000	G13	120-277, 347	50,000	180	5000	83	48	25
1763234	Y	VIV-T8DFSP4/17W/30/F	17	17	20	27	1800	2200	2900	G13	120-277, 347	50,000	180	3000	83	48	25
1763315	Y	VIV-T8DFSP4/17W/35/F	17	17	20	27	1850	2250	2950	G13	120-277, 347	50,000	180	3500	83	48	25
1763436	Y	VIV-T8DFSP4/17W/40/F	17	17	20	27	1900	2300	3000	G13	120-277, 347	50,000	180	4000	83	48	25
1763515	Y	VIV-T8DFSP4/17W/50/F	17	17	20	27	2000	2400	3100	G13	120-277, 347	50,000	180	5000	83	48	25
1763237	-	VIV-T8DFSP4/20W/30/F/SFT	20	20	23	30	1700	2100	2800	G13	120-277, 347	50,000	180	3000	83	60	25
1763318	-	VIV-T8DFSP4/20W/35/F/SFT	20	20	23	30	1750	2150	2850	G13	120-277, 347	50,000	180	3500	83	60	25
1763439	-	VIV-T8DFSP4/20W/40/F/SFT	20	20	23	30	1800	2200	2900	G13	120-277, 347	50,000	180	4000	83	60	25
1763517	-	VIV-T8DFSP4/20W/50/F/SFT	20	20	23	30	1900	2300	3000	G13	120-277, 347	50,000	180	5000	83	60	25