



Energy Advantage CDM Lamps with Allstart Technology

CDM205/U/O/4K/EA/ED28

Philips Energy Advantage CDM lamps with AllStart Technology is a high-efficiency protected “O” rated CDM lighting solution that provides energy savings without compromising light quality.

Warnings and Safety

- R "WARNING:These lamps can cause serious skin burn and eye inflammation from short wave ultraviolet radiation if outer envelope of the lamp is broken or punctured. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available." This lamp complies with FDA radiation performance standard 21 CFR subchapter J. (USA:21 CFR 1040.30 Canada: SOR/DORS/80-381)

Product data


General Information		Operating and Electrical	
Cap-Base	EX39 [Exclusionary Mogul Screw]	Luminous Efficacy (Rated) (Min)	88 lm/W
Operating Position	UNIVERSAL [Any or Universal (U)]	Luminous Efficacy (rated) (Nom)	95 lm/W
Features	Energy Advantage AllStart	Color rendering index (CRI)	84
Life to 50% Failures (Nom)	20,000 hour(s)	Mechanical and Housing	
Light Technical		Lamp Current (Nom)	1.9 A
Color Code	841 [CCT of 4100K]	Voltage (Nom)	128 V
Color Designation	4100 Kelvin		
Saturated Red (R9)	40	Bulb Finish	Clear
Chromaticity Coordinate X (Nom)	0.381	Bulb Shape	ED28
Chromaticity Coordinate Y (Nom)	0.384		

Energy Advantage CDM Lamps with Allstart Technology

Net Weight (Piece)	0.001 kg
Approval and Application	
Mercury (Hg) Content (Max)	38 mg
Product Data	
Order product name	CDM205/U/O/4K/EA/ED28
Full product name	CDM205/U/O/4K/EA/ED28

Order code	928601166003
Material Nr. (12NC)	928601166003
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677232566
Numerator - Packs per outer box	12
EAN/UPC - Case	50046677232561

Dimensional drawing



Product	D	D	L (min)	L (max)	L	C
CDM205/U/O/4K/EA/ED28	3.5 inch	89 mm	125 mm	129 mm	127 mm	8.313 inch

