

Perfect replacement to traditional halogen PAR and incandescent reflector lamps.

- ▶ PAR and BR are suitable for outdoor use (base up)
- ▶ Operating temperatures: -23°C/-10°F to 55°C/131°F



Order code	Description	Watts (W)	Base	Colour temp. (K)	CRI	Average life (hrs)	Initial lumens (lm)	Case qty	Hal/Incan equivalent (W)
PAR20*									
	MOL : 3 1/4 in. (95 mm) Dia. : 2 5/32 in. (63 mm)								
14100	CF9/27K/PAR20/E26/STD	9	E26	2 700	82	8 000	300	48	50
14101	CF9/30K/PAR20/E26/STD	9	E26	3 000	82	8 000	300	48	50
14102	CF9/35K/PAR20/E26/STD	9	E26	3 500	82	8 000	300	48	50
14103	CF9/41K/PAR20/E26/STD	9	E26	4 100	82	8 000	300	48	50
14104	CF9/50K/PAR20/E26/STD	9	E26	5 000	82	8 000	300	48	50
PAR30LN*									
	MOL : 4 29/32 in. (125 mm) Dia. : 3 1/4 in. (95 mm)								
60096	CF15/27K/PAR30LN/E26/STD	15	E26	2 700	82	8 000	700	24	75
14015	CF15/30K/PAR30LN/E26/STD	15	E26	3 000	82	8 000	700	24	75
14026	CF15/35K/PAR30LN/E26/STD	15	E26	3 500	82	8 000	700	24	75
61513	CF15/41K/PAR30LN/E26/STD	15	E26	4 100	82	8 000	700	24	75
14028	CF15/50K/PAR30LN/E26/STD	15	E26	5 000	82	8 000	700	24	75
PAR38*									
	MOL : 5 15/32 in. (139 mm) Dia. : 4 13/16 in. (122 mm)								
60944	CF23/27K/PAR38/E26/STD	23	E26	2 700	82	8 000	1 200	24	90
60097	CF23/30K/PAR38/E26/STD	23	E26	3 000	82	8 000	1 200	24	90
60098	CF23/35K/PAR38/E26/STD	23	E26	3 500	82	8 000	1 200	24	90
14013	CF23/41K/PAR38/E26/STD	23	E26	4 100	82	8 000	1 200	24	90
14014	CF23/50K/PAR38/E26/STD	23	E26	5 000	82	8 000	1 200	24	90
BR30*									
	MOL : 5 19/32 in. (142 mm) Dia. : 3 21/32 in. (93 mm)								
61081	CF16/27K/BR30/E26/STD	16	E26	2 700	82	10 000	750	24	60
BR40*									
	MOL : 6 13/32 in. (161 mm) Dia. : 4 13/16 in. (122 mm)								
14164	CF23/27K/BR40/E26/STD	23	E26	2 700	82	10 000	1 300	24	120
R20									
	MOL : 4 7/8 in. (124 mm) Dia. : 2 7/16 in. (62 mm)								
14162	CF11/27K/R20/E26/STD	11	E26	2 700	82	8 000	350	48	50
58397	CF14/27K/R20/E26/STD	14	E26	2 700	82	8 000	500	48	60



PAR-BR-R Lamps