# Eaton CGL-30

## Catalog Number: CGL-30

Eaton Bussmann series Tron CGL HRC form II Class C fuse, 600 Vac, 250 Vdc, 30A, 200 kAIC at 600 Vac, 40 kAIC 250 Vdc, Non Indicating, Current-limiting, HRC Form II, Blade end X blade end, Class C

#### General specifications



Eaton Bussmann series CGL fuse

**UPC** 

051712100328

Product Height

3.31 in

**Product Weight** 

0.115 lb

Compliances

Not Applicable

Catalog Number

CGL-30

Product Length/Depth

0.81 in

Product Width

0.94 in

Warranty

Not Applicable



### **Product specifications**

Fuse indicator

Non-indicating

Interrupt rating

200 kAIC at 600 Vac 40 kAIC 250 Vdc

Type

Current-limiting, HRC Form II

Connection

Blade end x blade end

Class

Class C

Voltage rating

600 Vac, 250 Vdc

Amperage Rating

30 A

Packaging type

Standard

#### Resources

#### Catalogs

Bussmann series complete full line catalog no. 1007

Bussmann series full line catalog 1007, section 05- IEC and British

Standard fuses

Multimedia

BS88 fuse link portfolio

Bussmann series Fuseology

Specifications and datasheets

Eaton Specification Sheet - CGL-30

Technical data sheets

CGL-30~LIMITRON FAST ACTING FUSE

Bussmann series CGL HRCII-C current-limiting fuses data sheet no. 4125

Technical service bulletins

Datasheet - FNQ-30



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia