

Notes

w1 07-16-2025 01:54:

Status	Discontinued	
Substitute	S49934R1	
Watts	11W	
Incandescent Equivalent	150W	
Fluorescent Equivalent	32W/30W/28W/25W	
Volts	Ballast Dependent	
Ballast Type	Туре А	
Shape	Т8	
Base	Medium Bi Pin	
ANSI Base	G13	
Nominal Length	48	
Finish	Gloss White	
CCT (Kelvin)	3000K	
Temperature	Warm White	
CRI	80+	
Lumens	1800L	
Beam Spread	210	
Dimmable	Yes-Dimmable	
Hours Rated	50000	
Product Category	Linear	
Technology	LED	

Electrical		
Ballasting Requirements	Ballast required	
Operating Frequency	50/60Hz	
Dimming Note	Only in Type A mode; Check Ballast MFG for Dimmer Compatibility	
Power Factor	0.9	
THD	20%	
Operating Temperature	-20C (-4F) to +45C (+113F)	

Physical	
MOL	47.78
MOD	1.1
Material	Glass
Lens Finish	Gloss White
Lens Material	Glass
Housing Color	White
Weight (lb.)	0.4

Additional information		
Tube Guard Use	Approved for use with tube guards when operated on Low or Normal ballast factor systems	
Installation Notes	Not for use in vapor tight fixtures.	
Rated For Enclosed Fixture	Yes	
Warranty	5-Years	

Compliance	
Safety Listing	cULus - Certified; cULus - Listed
Location Rating	Damp
DLC Approved	Yes
DLC ID	PL0FEUU1Y87D
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp