

G-24 / GX-24

FL423V-D1 13W 2 Pin Horizontal 2 Hole Screw Mount / **FL423V-D2** 18W 2 Pin Horizontal 2 Hole Screw Mount
FL423V-D3 26W 2 Pin Horizontal 2 Hole Screw Mount

G24 GX24 13W 18W 26W	- For 2 pin quad lamps - White polycarbonate body - Metal spring clip for positive lamp retention - Quick connect push-in wire terminals for 18 AWG Solid or Twist & Tin, stripped 3/8"	- Two wire ports per terminal to speed harness wiring - Two hole screw mount on base plate - Rated 75W, 600V - cCSAus Certified / cULus Listed
---	--	---

FL423V-Q Multi Wattage, Non-keyed, 2 Hole Screw Mount / **FL423V-Q1** 13W 4 Pin Horizontal 2 Hole Screw Mount
FL423V-Q2 18W 4 Pin Horizontal 2 Hole Screw Mount / **FL423V-Q3** 26/32W 4 Pin Horizontal 2 Hole Screw Mount
FL423V-Q3/4 26/32W/42W 4 Pin Horizontal 2 Hole Screw Mount / **FL423V-Q4** 42W 4 Pin Horizontal 2 Hole Screw Mount

G24 GX24 13W 18W 26/32W 42W	- For 4 pin electronic ballasted quad or triple tube lamps - White polycarbonate body 110°C rated - Metal spring clip for positive lamp retention - Quick connect push-in wire terminals for 18 AWG Solid or Twist & Tin or solder dipped	- wire, stripped 3/8" - Two wire ports per terminal to speed harness wiring - Two hole screw mount on base plate - Rated 75W, 600V - cCSAus Certified / cULus Listed
---	--	--

***Available in higher temperature material - 125C - Lexan 223R - ADD SUFFIX -223R to the part number**

FL423V-Q-BSI Multi Wattage, Non-keyed, Snap-In Mount / **FL423V-Q1-BSI** 13W 4 Pin Horizontal Snap-In Mount
FL423V-Q2-BSI 18W 4 Pin Horizontal Snap-In Mount / **FL423V-Q3-BSI** 26/32W 4 Pin Horizontal Snap-In Mount
FL423V-Q3/4-BSI 26/32W/42W 4 Pin Horizontal Snap-In Mount / **FL423V-Q4-BSI** 42W 4 Pin Horizontal Snap-In Mount

G24 GX24 13W 18W 26/32W 42W	- For 4 pin electronic ballasted quad or triple tube lamps - White polycarbonate body 110°C rated - Metal spring clip for positive lamp retention - Quick connect push-in wire terminals for 18 AWG Solid or Twist & Tin or solder dipped	- wire, stripped 3/8" - Two wire ports per terminal to speed harness wiring - Snap In mount on base plate - Rated 75W, 600V - cCSAus Certified / cULus Listed
---	--	---

***Available in higher temperature material - 125C - Lexan 223R - ADD SUFFIX -223R to the part number**