FIRE RATED
2 HOURS
UL-263

3 YEARS WARRANTY





FLP3.5G-8W-30K FLP3.5G-8W-40K


TECHNICAL SPECIFICATIONS


- Sizes: 4 3/4" dia. x 1 1/4" H
- Colours: WH-White, BS-Brushed steel, BK-Black
- 120 VOLTS / LED 8 WATTS
- 550 LUMENS
- Beam angle: 38° / CRI: > 80
- Degrees Kelvin: 3000K or 4000K
- 37/8" hole to be drilled
- Closed endorsement, IC for insulated ceilings
- Approved for damp locations
- Junction box for hardwiring and driver included

ACCESSORIES AVAILABLE


- Plaster frame **PF-378**
- 6 ft extension FLP-EX6

RECESSED LIGHTING DIMENSIONS






IUNCTION BOX DIMENSIONS




A: 3 ^{3/8}" / 85mm **B**: 3 ^{3/8}" / 85mm **C**: 1 ^{1/4}" / 32mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



AVERAGE BEAM ANGLE (50%): 37.1°
Unit: CD —— CO/180,37.1° —— C90/270,37.1°

FIGURE AAI



Note: The curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

♦ LUMIFARO


4300 Grande-Allée Blvd, Boisbriand QC, Canada J7H 1M9

450 979-0667

info@lumifaro.com www.lumifaro.com

CLIENT:		
PROJECT:		
DATE:		

EASY INSTALLATION



While our ultra-slim LED ceiling lights function with most dimmers and dimmers generally have a maximum 150-Watt rating for LED units, we strongly recommend that you not exceed 80% of this capacity in order to avoid lighting flicker when the dimmer is at its lowest setting. For example, we recommend a maximum of 8 6-inch units (120 Watts total) or 13 4-inch units (total 117 Watts).

CAUTION: ALWAYS CLOSE ELECTRICAL CURRENT BEFORE CONNECTING A LED DEVICE, otherwise the driver will be affected.