

# High-powered commercial downlight

Dals' new high-powered recessed downlight is a go-to for your commercial projects. With its five color temperatures to choose from, a cast aluminum housing, high lumen output, and indoor/outdoor rating, this can be installed just about anywhere. From clinics to schools and hotels to boutiques, this is the only slim recessed fixture you will need.



RECESSED



NEW

Model	Size	Watts	Delivered lumens	LED lumens	CRI	Color °T	Voltage
HPD4-CC	4"	20 W	1415 lm	1555 lm	90	2700, 3000, 3500, 4000, 5000 K	120 V
HPD6-CC	6"	30 W	2100 lm	2310 lm			
HPD8-CC	8"	40 W	2600 lm	2850 lm			

### Specifications

Every fixture includes a junction box with an integrated driver  
 Over 35,000 hours service life  
 Switch-selectable CCT: 2700 K/3000 K/3500 K/4000 K/5000 K  
 Smooth 360° wide spread  
 90° beam angle  
 Cast aluminum construction  
 Suitable for wet locations  
 Compatible with TRIAC, ELV and 0-10 V dimmers  
 Refer to website for dimmer compatibility  
 IC certification (suitable for direct contact with insulation)  
 Air-tight certified as per ASTM E283-04  
 5-year warranty

### Finish

○ WH White

### Options

#### HPD4-CC-V-WH

4" high-powered downlight with input for 0/10V, 120-277-347V

#### HPD6-CC-V-WH

6" high-powered downlight with input for 0/10V, 120-277-347V

#### HPD8-CC-V-WH

8" high-powered downlight with input for 0/10V, 120-277-347V

### Accessories

#### RFP-46 (HPD4, HPD6)

Rough-in plate

#### RFP-58 (HPD8)

Rough-in plate

### Order example


#### HPD6-CC


Dimmable 6" high-powered commercial downlight in a white finish

### Note

Other Color °T and Finishes available, but may require MOQ's and longer lead times. Please contact your DALI representative for more information.


#### HPD4-CC

Ø4 1/4" 



#### HPD6-CC

Ø6 1/2" 



#### HPD8-CC

Ø7 1/2" 

