



**JCD TYPE LAMPS** are line voltage (120-130 volt) halogen capsules with pin bases.

All STANDARD JCD lamps are safe to use in open fixtures due to their patented integral safety fuses.

The filament is well supported through glass pinch technology which minimizes deformation as well.

They are all made of UV stop quartz.



JCD  
(GY6.35)



MOL =  $1 \frac{13}{16}$  in. (46 mm)  
Dia. =  $\frac{1}{2}$  in. (13 mm)

JCD  
(G8)



MOL =  $1 \frac{13}{16}$  in. (46 mm)  
Dia. =  $\frac{1}{2}$  in. (13 mm)

JCD  
(GY8)



MOL =  $1 \frac{7}{8}$  in. (47.5 mm)  
Dia. =  $\frac{1}{2}$  in. (13 mm)

| Order code | Description                   | Watts<br>(W) | Base   | Volts<br>(V) | Colour/<br>Finish | Average<br>life<br>(hrs) | Initial<br>lumens<br>(lm) | Case<br>qty |
|------------|-------------------------------|--------------|--------|--------------|-------------------|--------------------------|---------------------------|-------------|
| <b>JCD</b> |                               |              |        |              |                   |                          |                           |             |
| 51045      | H20JCD/CL/2M/GY6.35/120V/STD  | 20           | GY6.35 | 120          | Clear             | 2 000                    | 180                       | 120         |
| 50879      | H35JCD/CL/2M/GY6.35/120V/STD  | 35           | GY6.35 | 120          | Clear             | 2 000                    | 380                       | 120         |
| 50878      | H50JCD/CL/2M/GY6.35/120V/STD  | 50           | GY6.35 | 120          | Clear             | 2 000                    | 600                       | 120         |
| 10317      | H75JCD/CL/2M/GY6.35/120V/STD  | 75           | GY6.35 | 120          | Clear             | 2 000                    | 1 050                     | 100         |
| 50877      | H100JCD/CL/2M/GY6.35/120V/STD | 100          | GY6.35 | 120          | Clear             | 2 000                    | 1 500                     | 100         |
| 55055      | H20JCD/CL/2M/G8/120V/STD      | 20           | G8     | 120          | Clear             | 2 000                    | 200                       | 100         |
| 10253      | H35JCD/CL/2M/G8/120V/STD      | 35           | G8     | 120          | Clear             | 2 000                    | 380                       | 120         |
| 10368      | H50JCD/CL/2M/G8/120V/STD      | 50           | G8     | 120          | Clear             | 2 000                    | 600                       | 120         |
| 15710      | JCD100W/130V/G8               | 100          | G8     | 130          | Clear             | 2 000                    | 1 600                     | 100         |
| 11266      | H25JCD/CL/2M/GY8/120V         | 25           | GY8    | 120          | Clear             | 2 000                    | 420                       | 50          |
| 11267      | H75JCD/CL/2M/GY8/120V         | 75           | GY8    | 120          | Clear             | 2 000                    | 1 300                     | 50          |
| 11265      | H100JCD/CL/2M/GY8/120V        | 100          | GY8    | 120          | Clear             | 2 000                    | 1 900                     | 50          |