



**JCD TYPE LAMPS** are line voltage (120-130 volt) halogen capsules with pin bases.

All STANDARD JCD lamps are safe to use in open fixtures due to their patented integral safety fuses.

The filament is well supported through glass pinch technology which minimizes deformation as well. They are all made of UV stop quartz.

JCD (GY6.35)



JCD (G8)



JCD (GY8)



| Order code                                       | Description                   | Watts<br>(W) | Base   | Volts<br>(V) | Colour/<br>Finish | Average<br>life<br>(hrs) | Initial<br>lumens<br>(lm) | Case<br>qty |
|--------------------------------------------------|-------------------------------|--------------|--------|--------------|-------------------|--------------------------|---------------------------|-------------|
| <b>JCD (GY6.35)</b>                              |                               |              |        |              |                   |                          |                           |             |
| MOL : 1 13/16 in. (46 mm) Dia. : 1/2 in. (13 mm) |                               |              |        |              |                   |                          |                           |             |
| 51045                                            | H20JCD/CL/2M/GY6.35/120V/STD  | 20           | GY6.35 | 120          | Clear             | 2 000                    | 180                       | 120         |
| 50879                                            | H35JCD/CL/2M/GY6.35/120V/STD  | 35           | GY6.35 | 120          | Clear             | 2 000                    | 380                       | 120         |
| 50878                                            | H50JCD/CL/2M/GY6.35/120V/STD  | 50           | GY6.35 | 120          | Clear             | 2 000                    | 600                       | 120         |
| 10317                                            | H75JCD/CL/2M/GY6.35/120V/STD  | 75           | GY6.35 | 120          | Clear             | 2 000                    | 1 050                     | 100         |
| 50877                                            | H100JCD/CL/2M/GY6.35/120V/STD | 100          | GY6.35 | 120          | Clear             | 2 000                    | 1 500                     | 100         |
| <b>JCD (G8)</b>                                  |                               |              |        |              |                   |                          |                           |             |
| MOL : 1 13/16 in. (46 mm) Dia. : 1/2 in. (13 mm) |                               |              |        |              |                   |                          |                           |             |
| 55055                                            | H20JCD/CL/2M/G8/120V/STD      | 20           | G8     | 120          | Clear             | 2 000                    | 200                       | 100         |
| 10253                                            | H35JCD/CL/2M/G8/120V/STD      | 35           | G8     | 120          | Clear             | 2 000                    | 380                       | 120         |
| 10368                                            | H50JCD/CL/2M/G8/120V/STD      | 50           | G8     | 120          | Clear             | 2 000                    | 600                       | 120         |
| 15710                                            | JCD100W/130V/G8               | 100          | G8     | 130          | Clear             | 2 000                    | 1 600                     | 100         |
| <b>JCD (GY8)</b>                                 |                               |              |        |              |                   |                          |                           |             |
| MOL : 1 7/8 in. (47.5 mm) Dia. : 1/2 in. (13 mm) |                               |              |        |              |                   |                          |                           |             |
| 11266                                            | H25JCD/CL/2M/GY8/120V         | 25           | GY8    | 120          | Clear             | 2 000                    | 420                       | 50          |
| 11267                                            | H75JCD/CL/2M/GY8/120V         | 75           | GY8    | 120          | Clear             | 2 000                    | 1 300                     | 50          |
| 11265                                            | H100JCD/CL/2M/GY8/120V        | 100          | GY8    | 120          | Clear             | 2 000                    | 1 900                     | 50          |



DIMMABLE



UV STOP

# JCD Lamps