# Liteline

# **LEDBAR-CCT**

LED Fluorobar, 290-1850 Lumens, 5-22W, Colour Selectable

Cove, Under Cabinet & Millwork

Job Information				
Project Name		Туре		
Location				
Quantity		Date		
Contact/Phone				
Notes				

# **Features**

# Housing

Durable extruded aluminum frame with frosted smooth lens. Suitable for dry location applications only. On-body ON/OFF switch and a 5-position 2700-5000K CCT select switch are provided for individual control..

#### LED Driver

Fixture is provided with built-in silent non-flicker electronic LED driver, 120V, 50 / 60Hz.

#### Light Output

Providing up to 1850 lumens, and up to 96lm/W, this undercabinet fixture also features a 5-position 2700-5000K CCT select switch.

#### Dimming

Fixture is 100~0% dimmable with industry standard TRIAC and ELV dimmers.

#### **LED Characteristics**

Powered by LED integrated strip that maintains uniform intensity with 70%

F

lumens at 60,000 hours with a rated life of 36,000 hours average life; at 90 CRI.

#### **Beam Spread**

The fixture lens provides for 125° beam spread.

#### Linking

Complete with a joiner, these no shadow linking fixtures can be linked up to 2500 mA / 300 W.

#### Mounting Kit

Hardware provided for mounting fixture to standard horizontal surfaces or vertical wall surface.

#### **Operating Temperature** -18°C~40°C (0°F~104°F).

### Rating

Suitable for use in closets. Compliant with NFPA 70, NEC section 410.16 (A)(1). Maintain a minimum of 6" clearance to combustible materials at all times.

SPECIFICATION			
Approved Location	Dry		
Beam Angle	125°		
CCT	2700 K / 3000 K / 3500 K / 4000 K / 5000 K		
Certification	cULus		
Connection Type	3-Wire		
CRI	90+		
Dimming	Yes		
Dimming Technology	TRIAC / ELV		
Lumens	Up to 1850		
Lumens per watt	Up to 96		
Min. Start Temp.	-18°C		
Lumen Maintenance	70% @ 60,000 hrs		
Power Factor	>0.95		
Rated Life	36,000 hrs		
THD	<15		
Voltage	120V		
Warranty	3 Years		
Wattage	Up to 22		

1800

1500



# Description

This LED Fluorobar light is a linear light with an integrated LED strip. Available with various lengths featuring ON/OFF and CCT Select switch to meet any installation application.

000 8 1" 25mm							
			LEDBAR14-CCT	LEDBAR23-CCT	LEDBAR34-CCT	LEDBAR46-CCT	LEDBAR58-CCT
Ì	Len	gth (L)	13½" 343mm	225⁄8" 574mm	347⁄16" 874mm	46³⁄ı₀" 1174mm	58" 1474mm
Í	Watta	age (W)	5	9	14	18	22
		2700 K	250	550	850	1000	1200
		3000 K	400	775	1175	1500	1800
	Lumens	3500 K	350	705	1120	1400	1600
		4000 K	400	775	1175	1500	1800

1175

775

# **Ordering Guide**

LEDBAR



5000 K

400

**34 :** 347/16", 14W **46 :** 463/16", 18W 58:58",22W

#### Notes:

Accessories are sold separately. For additional options consult your Liteline representative.

Due to our continued efforts to improve our products, product specifications are subject to change without notice.

Liteline Corporation	Telephone
Copyright © 2024	416.996.18
All rights reserved.	1.866.730.7

Fax 996.1856 905.709.5255 6.730.7704 1.888.738.9736



ŰŲĻ

Power (	Cord				
d -	<b>ALFT6000-WH-3</b> 6' Flexible 3-wire power cord for FluoroBar series.	"Of	<b>ALFT6000S-WH-3</b> 6' Flexible 3-wire power cord with on/off switch, for FluoroBar series.	20	<b>ALFT6016-WH-3</b> 16" Flexible 3-wire power cord for FluoroBar series.
Power 0	Cord with 90° Connector				
	ALFT60901-WH-3 6' Flexible 3-wire power cord with 90° connector (top connection).		<b>ALFT60902-WH-3</b> 6' Flexible 3-wire power cord with 90° connector (left connection).		ALFT60903-WH-3 6' Flexible 3-wire power cord with 90 connector (bottom connection).
	<b>ALFT60904-WH-3</b> 6' Flexible 3-wire power cord with 90° connector (right connection).				
Hardwi	re Box				
in inte	<b>ALFT6300-WH</b> Hardwire box for FluoroBar series, with on/off switch.		<b>ALFT6300-OS-WH</b> LEDBAR hardwire with motion sensor.		
Flexible	Cord with 90° Connectors				
	ALFT90-WH-3 6" Flexible 3-wire cord with 90° connectors (top connection).	t=d	ALFT901-WH-3 6" Flexible 3-wire cord with 90° connectors (left connection).	8d	<b>ALFT902-WH-3</b> 6" Flexible 3-wire cord with 90° connectors (bottom connection).
	<b>ALFT903-WH-3</b> 6" Flexible 3-wire cord with 90° connectors (right connection).				
Flexible	Connectors				
	<b>FBT6106-WH-3</b> 6" Flexible 3-wire connector.	6	<b>FBT6100-WH-3</b> 12" Flexible 3-wire connector.		<b>FBT6124-WH-3</b> 24" Flexible 3-wire connector
	FBT6136-WH-3 36" Flexible 3-wire connector				

# Clips



**LEDBAR-MAGCLIP-3** Magnetic mounting clips for LEDBAR, 3-pack.



**LEDBAR-CLIPS-90** 90° mounting clips for LEDBAR, 2-pack.