Universal Guards





On/Off Relays

Product #	Price	Volts 60 Hz	Resistive Charge (A)
Without transformer	r		
RC840	41.00	120/208/240	22
RC04U	41.00	347	18
R841D1036	79.00	600	10
With transformer			
RC840T-120	78.00	120	22
RC840T-240	56.00	208/240	22
RC840T-347	57.00	347	18
R841C1151	92.00	600	10

Note: Not recommended for fast-cycling modulated regulation (more than 6 cycles/hr). For fast-cycling heating equipment Solid State Relay.

Meant for external installation only. For installation inside heaters, refer to the options table

of the concerned product series.

Triac Relays

Product #	Price	Volts 60 Hz	Resistive Charge (A)	Input Signal
Without transf	ormer			
RT850	60.00	100 to 347	23	4-32VDC, 24VAC
CCT-25-1-C1	103.00	208/240/347	25	3-32VDC, 24VAC
CCT-30-1-C2	133.00	48-600	30	3-32VDC, 24VAC
With transform	ner			
RT850T-240	71.00	208/240	23	19.2/24VAC
RT850T-347	67.00	347	23	24VAC
CCT-25-1-C2-T	103.00	208/240/277/347	25	14.4/16.6/19.2/24VAC

Note: Meant for external installation only. For installation inside heaters, refer to the options table of the concerned product series.

Universal Guards

	Product #	Price	Description	Inside Dimension (Length X Height X Depth)
	F29-0143	40.00	Clear plastic thermostat guard	6 3/8 in. X 3 1/2 in. X 3 in.
	F29-0198	40.00		8 1/4 in. X 5 3/8 in. X 3 1/2 in.
-	F29-0193	65.00	Metal thermostat guard	6 in. X 3 13/16 in. X 3 1/8 in.