



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11342 - 6 Watt; MR16 LED; 4000K; GU5.3 base; 40 deg. Beam Angle; 24 Volt



GENERAL

Company	SATCO
EA Height	2.56
EA Width	1.97
EA Length	1.97
Candle Power	1200.0
Center Beam Candle Power	1200
Dimmable Text	Forward Phase or Reverse Phase; Check the transformer/driver MFG for dimmer compatibility
Lamp Filament	LED
Material	Metal / Plastic / Electronic Components
Fixture Type	MR
Status	Active
Style	Contemporary
CCT Selectable	No
Wattage Selectable	No
Finish Family	Gray
Amps	0.250-0.025A
Has Camera	No
IOT Enabled	No
Lens Finish	Gray
Lens Material	Plastic (PS)
Lensed	Yes
Operating Position	Universal
Photo Cell	No
Power Factor	0.92
SDS Class	LED_Lamp
Product Technology	LED
Incandescent Equivalent	50W

ELECTRICAL

CCT (Kelvin Temp)	4000K
Dimmable	Yes-Dimmable
Hours Rated	25000
Beam Angle (degree)	40
Color Temp	Cool White
CRI	80+
Dimming Type	Forward Phase or Reverse Phase
Operating Frequency	60Hz
Operating Temp	-25C (-13F) to +45C (+113F)
Lumens	550L
Volts	24V
Watts	6W

PHYSICAL

Lamp Base	Bi Pin GU5.3
Finish	Gray
Housing Color	Gray
ANSI Base	GU5.3
Lamp Type	MR16
MOD Lamps	1.97
MOL	1.772

ADDITIONAL INFO

Warranty	5-Years
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923113420
Case Cube	0.487
Case Height	6.5
Case Length	13.7
Case Quantity	48
Case UPC	10045923113427
Case Weight	6.24
Case Width	9.45
EA Cube	0.0057
EA Height	2.56
EA Length	1.97
EA Quantity	1
EA Weight	0.11
EA Width	1.97
Inner Cube	0.0886
Inner Height	5.51
Inner Length	6.42
Inner Quantity	12
Inner UPC	20045923113424
Inner Weight	1.48
Inner Width	4.33
Pack Type	Box
Web Length	1.772
Web Width	1.97

COMPLIANCE

Dark Sky Rated	No
FCC Compliant	Yes
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Listed
California Ban	Lawful for sale
DLC Approved	No
Title 20	Yes
T24 Compliant	No