

# Technical Information Bulletin

## Incandescent Lamps



Date: \_\_\_\_\_ Name of distributor: \_\_\_\_\_  
 In hands date of project: \_\_\_\_\_ Client #: \_\_\_\_\_  
 Project name/Number: \_\_\_\_\_ Name of end user: \_\_\_\_\_

### ORDERING INFORMATION

Order code: 67724  
 Description: 40A15/F/5M/130V/LOW TEMP/STD SM  
 UPC: 069549677241  
 Case quantity: 60

### PERFORMANCE DATA

Lamp type:	Appliance
Shape:	A15
Base:	Med Base E26
Filament:	C-9
Wattage (W):	40
Volts (V):	130
Initial lumens:	320
Average life (hours):	5 000
Finish:	Frosted
Protective coating:	Mylon
Maximum temperature °C (°F):	204°C (400°F)
Maximum Overall Length mm (in):	86.0 (3 3/8)
Light Center Length mm (in):	62.0 (2 7/16)



\*Initial lumens range: +/- 10 %

Qty	Description	Price

I accept the specifications of the lamp configuration mentioned above.

Name: \_\_\_\_\_  
 Company: \_\_\_\_\_  
 Signature: \_\_\_\_\_ Date: \_\_\_\_\_

Data is based upon tests performed in a controlled environment and representative of relative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.