



# SlimSurface LED Downlight

**SlimSurface LED downlight, 4-inch square, surface mount, 80 CRI, 3000K CCT, 650 lm,120V, Standard (TRIAC) dimming, wet location, Matte White Finish**

SlimSurface LED downlight, 4-inch square, surface mount, 80 CRI, 3000K CCT, 650 lm,120V, Standard (TRIAC) dimming, wet location, Matte White Finish - 71.8 lm/W

SlimSurface LED is a low profile downlight intended for ceiling or wall mount applications. This 0.625" thick luminaire offers the appearance of a recessed downlight but is actually surface mounted.

## Product data

General information	
Lamp Source Code	LED
Colour Temperature	3000 K
CRI	80
Downlight Type	Open Downlight
Photometric Distribution Type	Direct
Mounting	Surface Wall
Fixture Finish	White
Number Of Pieces	1
Grade	Value Grade

Operating and electrical	
Voltages	120 V
Luminaire Input Watts	10 W
Mechanical and housing	
Aperture Size Code	4 in
Fixture Size	4 in
Enclosure	Metal and Plastic
Approval and application	
Energy Certifications	Energy Star

## SlimSurface LED Downlight

Initial performance (IEC compliant)		Local code description	S4S830K7
Luminaire Lumens	650 lm	Numerator - Packs per outer box	1
Efficacy	71.8 lm/W	Material Nr. (12NC)	912401050024
Product data		Catalog Number	S4S830K7
Order product name	SLIM 4" SQUARE 600 LM 30K 80CRI 120V WHT	Catalog Number Description	SlimSurface LED downlight, 4-inch square, surface mount, 80 CRI, 3000K CCT, 650 lm,120V, Standard (TRIAC) dimming, wet location, Matte White Finish
EAN/UPC - Product	662057988801		
Order code	S4S830K7		
Numerator - Quantity Per Pack	1		

