

## ZENITH 60 Linear Pendant Direct Luminaire

ZNTH60-PD provides a direct lighting element in a sleek and contemporary pendant design. Selectable wattage and selectable CCT (Correlated Color Temperature) options offer enhanced flexibility.


Individual units are easily combined into row mounting with supplied joiner kits.

### Specifications

- Housing:** The Zenith60 housing is constructed of extruded aluminum 6063T5.
- End Caps:** Die cast aluminum fastened to housing with internal fasteners.
- Optics:** Frosted polycarbonate snap in lens with Lambertian distribution.
- Driver:** LED drivers for Direct outputs are contractor wattage selectable and universal 120-347V input (up to 3 different outputs – see output chart). Less than 20% THD and 0-10V dimmable down to 1%.
- Power Feed:** The unit comes complete with 18/5 STW 600V rated power cable (White or Black) preinstalled with internal quick connect. For row mounting the power feed is easily removed where not needed.
- Suspension:** Galvanized 1.5mm (1/16") aircraft cable with fully adjustable grippers for ease of on-site leveling. All suspension points are field adjustable along the length of a unit.
- LED:** Name brand LED with long life offered in standard 80+ CRI. On board selectable CCT offers maximum flexibility (3000K/3500K/4000K).
- Finish:** Polyester powder painted finish



### Dimensional Drawing



	L	W	H
4FT	47.24"	2.36"	3.35"
8FT	94.49"	2.36"	3.35"
6FT (optional)	70.86"	2.36"	3.35"

### Ordering Information Example: ZNTH60-PD/4/F/05L/MK3/80/UN3/D1/B/B6/S6/B

Family/ Series	Mounting	Function	Length	Diffuser Direct	Max Total Lumens	CCT 30K/35K/40K	CRI	Voltage	Driver	Housing Finish	Cord Colour/Length	Suspension Length	Canopy Colour	Options*											
ZNTH60	P	D	Direct	4	4ft	F	Frosted	05L	5000 (4ft)	MK3	80	UN3	120-347V	D1	0-10V Dim 1%	W	White	W6	White	S6	6ft	W	White	K1	White Cable kit
				8	8ft	10L	10000 (8ft)					B	Black	B6	6ft	B	Black	K2	Black Cable kit						
				C	Custom							C	Custom		Black 6ft	C	Custom	K4	Joiner Kit, Row mounting						

\* K1: 10Ft., Suspension, Power Cable White & 2 Aircraft Cable Kit

K2: 10Ft., Suspension, Power Cable Black & 2 Aircraft Cable Kit

**Light Outputs** Function: Direct

Catalogue Code	Voltage	Dimension			CCT	Efficacy lm/W	CRI	Direct		
		L	W	H				Watts	Delivered Lumens	Lumens per foot
ZNTH60-PD/4	120-347V	47.24"	2.36"	3.35"	30K/35K/40K	130	80+	40	5200	1300
								33	4290	1073
								25	3250	813
ZNTH60-PD/8	120-347V	94.49"	2.36"	3.35"	30K/35K/40K	130	80+	80	10400	1300
								66	8580	1073
								50	6500	813
ZNTH60-PD/C (6ft optional)	120-347V	70.86"	2.36"	3.35"	30K/35K/40K	130	80+	62	8060	1008
								54	7020	878
								46	5980	748